

ED4000 Series

ED4000M(A) Fire Listing Information



Corbin Russwin is pleased to announce the availability of a 3-hour fire rating listing for the ANSI/BHMA grade 1 ED4000M(A) series exit devices.

Designed for applications on narrow stile full glass, aluminum and metal doors in high-use and high-abuse situations, the ED4000M(A) series can now be used on door openings that require fire rated exit devices. Other features include a 3-1/2" wide stile design, heavy-duty construction, easy-to-use pushpad for quick egress and low projection for barrier-free code compliance.

Applications and Listings

Single Door	UL Listing	Maximum Opening	Application
Rim			
ED4200M	Panic	4' x *	Surface applied single-point latching.
ED4200MA	3 Hr.	4' x 8'	Surface applied single-point latching.
Rim - Delayed Egress			
ED4200MD	Panic	4' x *	Surface applied single-point latching.
ED4200MAD	3 Hr.	4' x 8'	Surface applied single-point latching.
SecureBolt®			
ED4200SM	Panic	4' x *	Surface applied single-point latching.
ED4200SMA	3 Hr.	4' x 8'	Surface applied single-point latching.
SecureBolt® - Delayed Egress			
ED4200SMD	Panic	4' x *	Surface applied single-point latching.
ED4200SMAD	3 Hr.	4' x 8'	Surface applied single-point latching.
Surface Vertical Rod			
ED4400M	Panic	4' x 10'	Surface applied two-point latching.
ED4400MA	3 Hr.	4' x 10'	Surface applied two-point latching.
Surface Vertical Rod - Delayed Egress			
ED4400MD	Panic	4' x 10'	Surface applied two-point latching.
ED4400MAD	3 Hr.	4' x 10'	Surface applied two-point latching.
Concealed Vertical Rod			
ED4800M	Panic	4' x 10'	Rods concealed in door two-point latching.
ED4800MA	3 Hr.	4' x 10'	Rods concealed in door two-point latching.
Concealed Vertical Rod - Delayed Egress			
ED4800MD	Panic	4' x 10'	Rods concealed in door two-point latching.
ED4800MAD	3 Hr.	4' x 10'	Rods concealed in door two-point latching.
Pair of Doors with Removable Mullion	UL Listing	Maximum Opening	Application
Rim x Rim			
ED4200M x ED4200M x 808	Panic	8' x 8'	Two independent active doors with removable mullion.
ED4200MA x ED4200MA x 808	3 Hr.	8' x 8'	Two independent active doors with removable mullion.
SecureBolt x SecureBolt			
ED4200SM x ED4200SM x 808	Panic	8' x 8'	Two independent active doors with removable mullion
ED4200SMA x ED4200SMA x 808	3 Hr.	8' x 8'	Two independent active doors with removable mullion

*UL does not set a door height limitation on panic applications.

ED4000 Series

ED4000M(A) Fire Listing Information



Pair of Doors	UL Listing	Maximum Opening	Application
Surface Vertical Rod			
ED4400M x ED4400M	Panic	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.
ED4400MA x ED4400MA	3 Hr.	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.
Surface Vertical Rod (Double Egress)			
ED4400M x ED4400M	Panic	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.
ED4400MA x ED4400MA	3 Hr.	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.
Concealed Vertical Rod			
ED4800M x ED4800M	Panic	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.
ED4800MA x ED4800MA	3 Hr.	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.
Concealed Vertical Rod (Double Egress)			
ED4800M x ED4800M	Panic	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.
ED4800MA x ED4800MA	3 Hr.	8' x 10'	Two independent doors with two-point latching, swinging in the same direction.

product bulletin