

# ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	<b>Norton Door Controls</b>
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-ASA-20150068-IBA1-EN
Issue date	10.04.2015
Valid to	09.04.2015




**Door Closer – Norton 7500 series**

**ASSA ABLOY / Norton Door Controls**

[www.bau-umwelt.com](http://www.bau-umwelt.com) / <https://epd-online.com>



### 1. General Information

<p><b>Norton Door Controls</b></p> <hr/> <p><b>Programme holder</b>          IBU - Institut Bauen und Umwelt e.V.          Panoramastr. 1          10178 Berlin          Germany</p> <hr/> <p><b>Declaration number</b>          EPD-ASA-20150068-IBA1-EN</p> <hr/> <p><b>This Declaration is based on the Product Category Rules:</b>          Locks and fittings, 07.2014</p> <p>(PCR tested and approved by the independent expert committee (SVR))</p> <hr/> <p><b>Issue date</b>          10.04.2015</p> <hr/> <p><b>Valid to</b>          09.04.2020</p> <p></p> <hr/> <p>Prof. Dr.-Ing. Horst J. Bossenmayer          (President of Institut Bauen und Umwelt e.V.)</p> <hr/> <p></p> <hr/> <p>Dr.-Ing. Burkhard Lehmann          (Managing Director IBU)</p>	<p><b>Door Closer – Norton 7500 Series</b></p> <hr/> <p><b>Owner of the Declaration</b>          Norton Door Controls          3000 Hwy 74 East          Monroe, NC 28112 USA</p> <hr/> <p><b>Declared product / Declared unit</b>          The declaration represents 1 Rack-and-Pinion hydraulic door closer (7500 Series), consisting of the following items:          - A closer body          - A closer arm          - Accessories</p> <hr/> <p><b>Scope:</b>          This declaration and its LCA study are relevant to Norton Door Controls 7500 series door closers.          The primary manufacturing processes are made by external suppliers and the final manufacturing processes and assembly for all door closer components occur at our manufacturing factory in Monroe, NC USA.</p> <hr/> <p><b>Verification</b></p> <p>The CEN Standard EN 15804 serves as the core PCR</p> <p>Independent verification of the declaration and data according to ISO 14025</p> <p><input type="checkbox"/> internally    <input checked="" type="checkbox"/> externally</p> <hr/> <p></p> <hr/> <p>Dr. Wolfram Trinius          (Independent verifier appointed by SVR)</p>
--	---

### 2. Product

#### 2.1 Product description

Product name: Norton 7500 door closers.

Product characteristic: closers are UL Listed and characterized by:

- Cast aluminum body with a rack-and-pinion design
- 7500 Series has adjustable spring sizes 1 through 6 (ADA Compliant)
- 7500 Series is Tri-Style® packaged for regular, top jamb or parallel arm mounting.
- Non-handed
- Rack-and-pinion design
- Cast Aluminum body
- Adjustable closing force and two closing ranges
- Adjustable back check, which offers optimum protection for doors and walls by damped opening
- Adjustable delayed closing which is important for situations where extended closing time is needed for passing through a door
- Self-drilling screws

- Wide range of accessories.

This EPD is applicable to following products: 7500 series.

#### 2.2 Application

The Norton Door Controls door closer 7500 Series can be used – from private to commercial and public sectors both light and heavy:

- Fire & smoke protection and standard doors
- For interior doors
- For interior side of exterior doors
- 7500 series are Tri-Style® packed (for regular, top jamb, or parallel mounting) non-handed allowing for push or pull side left or right hand mounting.

#### 2.3 Technical Data

For the declared product, the following technical data in the delivery status must be provided with reference to the test standard.

**Technical data**

Name	Value
Adjustable closing force	ANSI/BHMA A156.4 Size 1 - 6
Door width up to	interior - 54 in (1370 mm) exterior - 48 in (1220 mm)
Door weight up to	250 lbs (114 kg)
Fire and smoke protections	Yes
Door swing directions	Non-handed (left or right hand mounted)
Closing speed	Variable between 180° - 10°
Latching speed	Variable between 10° - 0°
Back check	Variable above 70°
Opening angle	Up to 180° depending on arm application
Closer weight	5.52 lbs (2.50 kg)
Closer height	3.88 in (98 mm)
Closer depth	2.13 in (54 mm)
Closer length	13.63 in (346 mm)
Certified to / in compliance with	ANSI/BHMA A156.4 Grade 1 UL Listed UL10C for positive pressure fire doors ADA compliant

**2.4 Placing on the market / Application rules**

The standards that can be applied for door closer devices and relevant accessories are:  
ANSI/BHMA A156.4 Grade 1 for Door Controls - Closers  
UL Listed product  
ADA Compliant  
Exceeds 15 million cycles  
7500 series door closers and relevant accessories are certified according to these standards.

**2.5 Delivery status**

Door closer units and arms are delivered ready for installation. The door closer unit including the packaging has the following dimensions: 387 mm x 156 mm x 89 mm.

**2.6 Base materials / Ancillary materials**

The primary product components and/or materials must be indicated as a percentage mass to enable the user of the EPD to understand the composition of the product in delivery status.  
The average composition for Norton Door Controls 7500 Series closers, including the arm is as following:

Component	Percentage in mass (%)
Aluminum	19.58
Brass	0.39
Steel	66.26
Plastic	7.56
Other	6.21
Total	100.0

**2.7 Manufacture**

The primary manufacturing processes are made by Tier 1 suppliers located in China, Taiwan, Mexico, and throughout the USA and some primary and the final manufacturing processes occur at factory in Monroe, NC USA. The components come from processes like

stamped steel, turning, zinc, forging and aluminum casting. Final assembly takes place in Monroe, NC USA.

The factory of Monroe, NC USA has a certification of Quality Management system in accordance with ISO 9001:2008.

Waste management at the Monroe, NC USA factory is in accordance with the plant's ISO9001 and ISO14001 standards:

- Office paper / cardboard recycling - covered under Solid Waste Recycling Program
- Plant paper / cardboard recycling - covered under Solid Waste Recycling Program
- General trash - covered under Solid Waste Recycling Program
- Comingled recyclables - covered under Solid Waste Recycling Program
- Metals recycling - metal chips and dust - covered under Solid Waste Recycling Program
- Wood pallets - covered under Solid Waste Recycling Program

**2.8 Environment and health during manufacturing**

ASSA ABLOY and Norton Door Controls are committed to producing and distributing door opening solutions with minimal environmental impact, where health & safety is the primary focus for all employees and associates.

- Environmental operations, GHG, energy, water, waste, VOC, surface treatment and H&S are being routinely monitored. Inspections, audits, and reviews are conducted periodically to ensure that applicable standards are met and Environment Management program effectiveness is evaluated.
- Code of Conduct covers human rights, labor practices and decent work. Management of ASSA ABLOY and Norton Door Controls are aware of their environmental roles and responsibilities, providing appropriate training, supporting accountability and recognizing outstanding performance.

- The factory in Monroe, NC USA has certification of Environmental Management to ISO 14001:2004.
- Any waste metals during machining are separated and recycled. The waste from the water-based painting process is delivered to waste treatment plant.

**2.9 Product processing / Installation**

Norton Door Controls 7500 series door closers are sold through a variety of distribution and wholesale sources and installed by trained installation technicians, such as locksmiths, carpenters etc. adhering to local/national standards and requirements as well as unskilled laborers. In any case the installation must be done in line with instructions provided by the manufacturer.

Door and frame preparations are made in door manufacturer's production sites or on the job site.

**2.10 Packaging**

Norton Door Controls 7500 series door closers are packed in cardboard packaging. Packaging includes

paper installation instruction – all of which are fully recyclable.

40% + of carton is made from recycled material  
100% of paper documents are made from recycled material.

Material	Value (%)
Cardboard/paper	100.0
Total	100.0

### 2.11 Condition of use

Annual inspection is recommended in order to guarantee correct functionality of the product and the door leaf. The inspection includes: checking, fixing screws to ensure they are properly tight, correct adjustments (closing speeds, force), compliance with local legal inspection standards and greasing all the moving parts of the arm.

### 2.12 Environment and health during use

There is no harmful emissive potential. No damage to health or impairment is expected under normal use corresponding to the intended use of the product.

### 2.13 Reference service life

Norton Door Controls 7500 Series door closers were developed to comply with ANSI/BHMA A156.4 Grade 1 standard and quality requirements. The 7500 door closer has surpassed 10 million cycles in testing witnessed and verified by UL. This closer exceeds ANSI/BHMA A156.4 Grade 1 cycle requirements by more than 6 times. The typical life time of a 7500 is 25 years, dependent on frequency of cycles.

### 2.14 Extraordinary effects

#### Fire

Norton Door Controls 7500 series door closers are tested for usage in fire and smoke protection doors according to UL10C.

#### Water

Door closers include hydraulic oil and are designed for conventional use and are not intended for flood protection. Unforeseeable flooding conditions will increase the potential for developing surface rust.

#### Mechanical destruction

No danger to the environment can be anticipated during mechanical destruction.

### 2.15 Re-use phase

It is possible to re-use the product during the reference service life and to move it from one door to another. The majority, by weight, of components is aluminum alloy, steel which can be recycled. The plastic components can be used for energy recovery within a waste incineration process.

Norton Door Controls has a Product End-of-Life Recycle Program where product can be returned to Norton for proper recycling/disposal. Once received product is separated and recycled/disposed according to the Solid Waste Recycling Program guidelines.

### 2.16 Disposal

Lacquer and lubricants contained in the product were treated as a waste for landfill.

### 2.17 Further information

Norton Door Controls  
3000 Hwy 74 East  
Monroe, NC 28112 USA  
Tel: +800-438-1951  
www.nortondoorcontrols.com

## 3. LCA: Calculation rules

### 3.1 Declared Unit

The declaration refers to the functional unit of 1 piece of door closer 7500 Series as specified in Part B requirements on the EPD PCR Locks and fittings.

#### Declared unit

Name	Value	Unit
Declared unit	4.137	Piece of door closer
Conversion factor to 1 kg	0.241	-

### 3.2 System boundary

Type of the EPD: cradle to gate - with Options  
The following life cycle phases were considered:

#### Production stage:

- A1 – Raw material extraction and processing
- A2 – Transport to the manufacturer and
- A3 – Manufacturing

#### A4-A5 Construction stage:

- A4 - Transport from the gate to the site
- A5 – Packaging waste processing

#### End-of-life stage:

- C2 – Transport to waste processing
- C3 – Waste processing
- C4 – Disposal (landfill)

This includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of waste state or disposal of final residues.

- D - Declaration of all benefits or recycling potential from EOL and A5.

### 3.3 Estimates and assumptions

In the End-of-Life phase a scenario with collection rate of 100% for all the recyclable materials was assumed.

### 3.4 Cut-off criteria

In the assessment, all available data from the production process are considered, i.e. all raw materials used, auxiliary materials (e.g. lubricants), thermal energy consumption and electric power consumption - including material and energy flows contributing less than 1% of mass or energy (if available). In case a specific flow contributing less than

1% in mass or energy is not available, worst case assumption proxies are selected to represent the respective environmental impacts.

Impacts relating to the production of machines and facilities required during production are out of the scope of this assessment.

### 3.5 Background data

For life cycle modeling of the considered products, the GaBi 6 Software System for Life Cycle Engineering, developed by PE INTERNATIONAL AG, is used /GaBi 6 2013/. The GaBi-database contains consistent and documented datasets which are documented in the online

GaBi-documentation /GaBi 6 2013D/.

To ensure comparability of results in the LCA, the basic data of GaBi database were used for energy, transportation and auxiliary materials.

### 3.6 Data quality

The requirements for data quality and background data correspond to the specifications of the /IBU PCR PART A/.

PE INTERNATIONAL performed a variety of tests and checks during the entire project to ensure high quality of the completed project. This obviously includes an extensive review of project-specific LCA models as well as the background data used.

The technological background of the collected data reflects the physical reality of the declared products. The datasets are complete and conform to the system boundaries and the criteria for the exclusion of inputs

and outputs.

All relevant background datasets are taken from the GaBi 6 software database. The last revision of the used background data has taken place not longer than 10 years ago.

### 3.7 Period under review

The period under review is 2013/14 (12 month average).

### 3.8 Allocation

Regarding incineration, the software model for the waste incineration plant (WIP) is adapted according to the material composition and heating value of the combusted material. In this EPD the following specific life cycle inventories for the WIP are considered:

- Waste incineration of plastic
- Waste incineration of paper
- Waste incineration of wood

Regarding the recycling material of metals, the metal parts in the EoL are declared as end-of-waste status. Thus, these materials are considered in module D. Specific information on allocation within the background data is given in the GaBi dataset documentation.

### 3.9 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

## 4. LCA: Scenarios and additional technical information

The following technical information is a basis for the declared modules or can be used for developing specific scenarios in the context of a building assessment if modules are not declared (MND).

### Installation into the building (A5)

Name	Value	Unit
Output substances following waste treatment on site (Paper packaging)	0.42	kg

### Reference service life

Name	Value	Unit
Reference service life	25	a

### End of life (C1-C4)

Name	Value	Unit
Collected separately Aluminum, brass, steel, plastics	3.88	kg
Collected as mixed construction waste – construction waste for landfilling	0.26	kg
Reuse plastics parts	0.31	kg
Recycling Aluminum, brass, steel	3.57	kg
Landfilling - Construction waste for landfilling	0.26	kg

### Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Collected separately waste type Door closer (including packaging)	4.55	kg

Recycling Aluminium	17.79	%
Recycling Brass	0.35	%
Recycling Steel	60.21	%
Thermal Treatment (plastics)	6.88	%
Loss Construction waste for landfilling (no recycling potential)	5.61	%
Reuse Packaging (paper) (from A5)	9.16	%

**5. LCA: Results**

Results shown below were calculated using CML Methodology.

**DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)**

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement <sup>1)</sup>	Refurbishment <sup>1)</sup>	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	X	X	X	X

**RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 piece of Norton 7500**

Parameter	Unit	A1 - A3	A4	A5	C2	C3	C4	D
Global warming potential	[kg CO <sub>2</sub> -Eq.]	2.21E+01	1.30E-01	5.91E-01	1.30E-01	0.00E+00	6.47E-01	-1.26E+01
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	4.74E-09	6.22E-13	2.70E-12	6.22E-13	0.00E+00	1.95E-12	3.53E-09
Acidification potential of land and water	[kg SO <sub>2</sub> -Eq.]	1.00E-01	5.95E-04	1.35E-04	5.95E-04	0.00E+00	1.65E-04	-6.02E-02
Eutrophication potential	[kg (PO <sub>4</sub> ) <sup>3-</sup> - Eq.]	7.48E-03	1.36E-04	2.35E-05	1.36E-04	0.00E+00	1.25E-05	-3.45E-03
Formation potential of tropospheric ozone photochemical oxidants	[kg Ethen Eq.]	8.55E-03	-1.92E-04	9.55E-06	-1.92E-04	0.00E+00	8.00E-06	-4.95E-03
Abiotic depletion potential for non fossil resources	[kg Sb Eq.]	6.85E-05	4.90E-09	1.07E-08	4.90E-09	0.00E+00	4.27E-08	-1.49E-05
Abiotic depletion potential for fossil resources	[MJ]	2.60E+02	1.79E+00	1.65E-01	1.79E+00	0.00E+00	2.74E-01	-1.20E+02

**RESULTS OF THE LCA - RESOURCE USE: 1 piece of Norton 7500**

Parameter	Unit	A1 - A3	A4	A5	C2	C3	C4	D
Renewable primary energy as energy carrier	[MJ]	5.67E+01	-	-	-	-	-	-
Renewable primary energy resources as material utilization	[MJ]	0.00E+00	-	-	-	-	-	-
Total use of renewable primary energy resources	[MJ]	5.67E+01	7.07E-02	1.54E-02	7.07E-02	0.00E+00	2.00E-02	-3.24E+01
Non renewable primary energy as energy carrier	[MJ]	3.07E+02	-	-	-	-	-	-
Non renewable primary energy as material utilization	[MJ]	0.00E+00	-	-	-	-	-	-
Total use of non renewable primary energy resources	[MJ]	3.07E+02	1.80E+00	1.94E-01	1.80E+00	0.00E+00	3.04E-01	-1.38E+02
Use of secondary material	[kg]	7.11E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	[MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non renewable secondary fuels	[MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	[m <sup>3</sup> ]	1.43E-01	4.99E-05	1.72E-03	4.99E-05	0.00E+00	1.58E-03	-8.99E-02

**RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES: 1 piece of Norton 7500**

Parameter	Unit	A1 - A3	A4	A5	C2	C3	C4	D
Hazardous waste disposed	[kg]	6.10E-03	4.10E-06	1.33E-05	4.10E-06	0.00E+00	2.12E-05	1.51E-03
Non hazardous waste disposed	[kg]	1.56E+00	2.26E-04	1.48E-02	2.26E-04	0.00E+00	6.03E-02	-1.31E+00
Radioactive waste disposed	[kg]	1.85E-02	2.36E-06	1.13E-05	2.36E-06	0.00E+00	1.21E-05	-7.48E-03
Components for re-use	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-
Materials for recycling	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.30E+00	0.00E+00	-
Materials for energy recovery	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-
Exported electrical energy	[MJ]	0.00E+00	0.00E+00	7.47E-01	0.00E+00	0.00E+00	1.24E+00	-
Exported thermal energy	[MJ]	0.00E+00	0.00E+00	2.11E+00	0.00E+00	0.00E+00	3.39E+00	-

### 6. LCA: Interpretation

This chapter contains an interpretation of the Life Cycle Impact Assessment categories. Stated percentages in the whole interpretation are related to the overall life cycle, excluding credits (module D).

Production phase (module A1-A3) contributes between 94 and 100% to total impact assessment. This stage is dominated by upstream emissions associated with steel- and secondary aluminum manufacturing processes. Steel accounts with app. 66% to the overall mass of the product, therefore, the impacts are in line with the mass composition of the product.

The environmental impacts for the transport (A2) have a negligible impact within this stage.

In the end-of-life phase, there are loads and benefits (module D, negative values) considered. The benefits are considered beyond the system boundaries and are declared for the recycling potential of the metals and for the credits from the incineration process (energy substitution).

### 7. Requisite evidence

Not applicable in this EPD.

### 8. References

#### Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin (pub.):  
Generation of Environmental Product Declarations  
(EPDs);

#### General principles

for the EPD range of Institut Bauen und Umwelt e.V.  
(IBU), 2013-04  
[www.bau-umwelt.de](http://www.bau-umwelt.de)

#### IBU PCR Part A

IBU PCR Part A: Institut Bauen und Umwelt e.V.,  
Königswinter (pub.): Product Category Rules for  
Construction Products from the range of Environmental  
Product Declarations of Institut Bauen und Umwelt  
(IBU), Part A: Calculation Rules for the Life Cycle  
Assessment and Requirements on the Background  
Report. April 2013  
[www.bau-umwelt.de](http://www.bau-umwelt.de)

#### IBU PCR Part B

IBU PCR Part B: PCR Guidance-Texts for Building-  
Related Products and Services. From the range of  
Environmental Product Declarations of Institute  
Construction and Environment e.V. (IBU). Part B:  
Requirements on the EPD for Locks and fittings.  
[www.bau-umwelt.com](http://www.bau-umwelt.com)

#### ADA Compliant

ADA Compliant: Americans with Disabilities Act 2010  
Standard for Accessible Design

#### ANSI/BHMA A156.4

ANSI/BHMA A156.4-2013: Standard for Door Controls  
- Door Closers

#### DIN EN 1154

DIN EN 1154: Building hardware - Controlled door  
closing devices - Requirements and test methods  
(includes amendment A1:2002)

#### DIN EN ISO 9001

DIN EN ISO 9001:2008: Quality management systems  
- Requirements; Trilingual version EN ISO 9001:2008

#### DIN EN ISO 14001

DIN EN ISO 14001: Environmental management  
systems - Requirements with guidance for use  
(ISO 14001:2004 + Cor. 1:2009)

#### DIN EN ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and  
declarations — Type III environmental declarations —  
Principles and procedures

#### EN 15804

EN 15804:2012+A1:2014: Sustainability of  
construction works - Environmental product  
declarations - Core rules for the product category of  
construction products

#### GaBi 6 2013

GaBi 6 2013: Software-System and Database for Life  
Cycle Engineering. Copyright, TM. Stuttgart,  
Echterdingen, 1992-2013.

#### GaBi 6 2013D

GaBi 6 2013D: Documentation of GaBi 6: Software-  
System and Database for Life Cycle Engineering.  
Copyright, TM. Stuttgart, Echterdingen, 1992-2013.  
<http://documentation.gabi-software.com/>

#### UL Listed

Tested to / Compliant with UL228 Standard for Door  
Closers - Holders

#### UL10C

UL10C Positive Pressure Fire Test of Door Assemblies

**9. Annex**

Results shown below were calculated using TRACI Methodology.

**DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)**

PRODUCT STAGE		CONSTRUCTION PROCESS STAGE			USE STAGE								END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement <sup>(1)</sup>	Refurbishment <sup>(1)</sup>	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	

**RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 piece of Norton 7500**

Parameter	Parameter	Unit	A1-3	A4	A5	C2	C3	C4	D
GWP	Global warming potential	[kg CO <sub>2</sub> -Eq.]	2.21E+01	1.30E-01	5.91E-01	1.30E-01	0.00E+00	6.47E-01	-1.26E+01
ODP	Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	5.04E-09	6.62E-13	2.87E-12	6.62E-13	0.00E+00	2.07E-12	3.76E-09
AP	Acidification potential of land and water	[kg SO <sub>2</sub> -Eq.]	9.86E-02	7.77E-04	1.63E-04	7.77E-04	0.00E+00	1.93E-04	-5.76E-02
EP	Eutrophication potential	[kg N-eq.]	4.22E-03	5.46E-05	9.20E-06	5.46E-05	0.00E+00	5.51E-06	-1.74E-03
Smog	Ground-level smog formation potential	[kg O <sub>3</sub> -eq.]	1.23E+00	1.60E-02	3.81E-03	1.60E-02	0.00E+00	1.52E-03	-6.13E-01
Resources		[MJ]	1.96E+01	2.58E-01	1.94E-02	2.58E-01	0.00E+00	2.82E-02	-6.48E+00

**RESULTS OF THE LCA - RESOURCE USE: 1 piece of Norton 7500**

Parameter	Parameter	Unit	A1-3	A4	A5	C2	C3	C4	D
PERE	Renewable primary energy as energy carrier	[MJ]	5.67E+01	-	-	-	-	-	-
PERM	Renewable primary energy resources as material utilization	[MJ]	0.00E+00	-	-	-	-	-	-
PERT	Total use of renewable primary energy resources	[MJ]	5.67E+01	7.07E-02	1.54E-02	7.07E-02	0.00E+00	2.00E-02	-3.24E+01
PENRE	Non renewable primary energy as energy carrier	[MJ]	3.07E+02	-	-	-	-	-	-
PENRM	Non renewable primary energy as material utilization	[MJ]	0.00E+00	-	-	-	-	-	-
PENRT	Total use of non renewable primary energy resources	[MJ]	3.07E+02	1.80E+00	1.94E-01	1.80E+00	0.00E+00	3.04E-01	-1.38E+02
SM	Use of secondary material	[kg]	7.11E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	Use of renewable secondary fuels	[MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	Use of non renewable secondary fuels	[MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	Use of net fresh water	[m <sup>3</sup> ]	1.43E-01	4.99E-05	1.72E-03	4.99E-05	0.00E+00	1.58E-03	-8.99E-02

**RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES: 1 piece of Norton 7500**

Parameter	Parameter	Unit	A1-3	A4	A5	C2	C3	C4	D
HWD	Hazardous waste disposed	[kg]	6.10E-03	4.10E-06	1.33E-05	4.10E-06	0.00E+00	2.12E-05	1.51E-03
NHWD	Non hazardous waste disposed	[kg]	1.56E+00	2.26E-04	1.48E-02	2.26E-04	0.00E+00	6.03E-02	-1.31E+00
RWD	Radioactive waste disposed	[kg]	1.85E-02	2.36E-06	1.13E-05	2.36E-06	0.00E+00	1.21E-05	-7.48E-03
CRU	Components for re-use	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-
MFR	Materials for recycling	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.30E+00	0.00E+00	-
MER	Materials for energy recovery	[kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-
EEE	Exported electrical energy	[MJ]	0.00E+00	0.00E+00	7.47E-01	0.00E+00	0.00E+00	1.24E+00	-
EET	Exported thermal energy	[MJ]	0.00E+00	0.00E+00	2.11E+00	0.00E+00	0.00E+00	3.39E+00	-



**Norton**

**ASSA ABLOY**



**Publisher**

Institut Bauen und Umwelt e.V.  
Panoramastr. 1  
10178 Berlin  
Germany

Tel +49 (0)30 3087748-0  
Fax +49 (0)30 3087748-29  
Mail [info@bau-umwelt.com](mailto:info@bau-umwelt.com)  
Web [www.bau-umwelt.com](http://www.bau-umwelt.com)



**Programme holder**

Institut Bauen und Umwelt e.V.  
Panoramastr 1  
10178 Berlin  
Germany

Tel +49 (0)30 3087748-0  
Fax +49 (0)30 3087748-29  
Mail [info@bau-umwelt.com](mailto:info@bau-umwelt.com)  
Web [www.bau-umwelt.com](http://www.bau-umwelt.com)



**PE INTERNATIONAL**  
SUSTAINABILITY PERFORMANCE

**Author of the Life Cycle Assessment**

PE INTERNATIONAL AG  
Hauptstraße 111-113  
70771 Leinfelden-Echterdingen  
Germany

Tel +49 (0)711 341817-0  
Fax +49 (0)711 341817-25  
Mail [info@pe-international.com](mailto:info@pe-international.com)  
Web [www.pe-international.com](http://www.pe-international.com)

**Norton**

**ASSA ABLOY**

**Owner of the Declaration**

Norton Door Controls  
3000 Hwy 74 East  
Monroe, NC 28112  
USA

Tel +1 800-438-1951  
Fax +1 800-338-0965  
Web [www.nortondoорcontrols.com](http://www.nortondoорcontrols.com)  
[www.assaabloydss.com](http://www.assaabloydss.com)